



25227B

2 Conductor 12AWG Unshielded CL3P Rated
Audio, Control, and Low Voltage Power

Construction & Dimenstions

CONDUCTOR PARAMETERS	
Number Of Conductors	2
AWG Size	12
Conductor Stranding	19x25
Conductor Type	Bare copper
Nominal DCR	1.7 Ohm/1000ft
Cabling Lay Length	4.25 in
INSULATION PARAMETERS	
Insulation Type	Plenum PVC
Insulation Thickness	0.012 in
Insulation Color Code	1. Black 2.White
SHIELDING PARAMETERS	
Shield Type	None
ELECTRICAL CHARACTERISTICS	

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	Flexible Plenum
Jacket Thickness	0.015 in
Nominal Cable O.D.	0.263 in
Plenum	Yes
NEC UL Rating	CL3P, FPLP
RoHS Compliant	Yes
Pull Tension	146 lbs
Bend Radius	2.367 in
Cable Weight	54 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60 Deg C
UL Voltage Rating	300



25227B

Related Products

RELATED PRODUCTS	
Non Plenum Number	227
Aquaseal Direct Burial Number	AQ227
4 Pole SpeakOn	CN-NL4FC
SpeakOn Panel Mount	CN-NL4MP