


**29507 Multi-Conductor - 1000V UL Flexible Motor Supply Cable**

For more Information  
please call

1-800-Belden1

**Description:**

4-cond. (3) stranded tinned copper circuit conductors plus (1) ground wire with PVC insulation, XLPE insulation, overall Duofoil® (100% cov.) plus a tinned copper braid shield (85% cov.), tinned copper sectioned drain wire, Sun-&oil-resistant PVC jacket.

**Usage (Overall)**

**Suitable Applications:** AC Motor Drives, VFD, Variable Frequency Drive

**Physical Characteristics (Overall)****Conductor**

**AWG:**

# Conductors	AWG	Stranding	Conductor Material
3	2	7x19x23	TC - Tinned Copper

**Ground Wire**

<b>Ground Wire (Y/N):</b>	Y
<b>Ground Wire AWG:</b>	2
<b>Ground Wire Stranding:</b>	7x19x23
<b>Ground Wire Conductor Material:</b>	TC - Tinned Copper
<b>Ground Wire Insulation Material:</b>	PVC - Polyvinyl Chloride

**Insulation**

**Insulation Material:**

Insulation Material	Wall Thickness (in.)
XLPE - Cross Linked Polyethylene	.060

**Insulation Resistance:** 300 Megaohms/1000 ft.

**Outer Shield**

**Outer Shield Material:**

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	85

**Outer Shield Drain Wire AWG:**

AWG	Stranding	Drain Wire Conductor Material
8 (4x)	133x29	TC - Tinned Copper

**Outer Jacket**

**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

**Overall Cable**

**Overall Nominal Diameter:** 1.310 in.

**Mechanical Characteristics (Overall)**

<b>UL Temperature Rating:</b>	90°C Wet/Dry
<b>Bulk Cable Weight:</b>	1630 lbs/1000 ft.

**29507 Multi-Conductor - 1000V UL Flexible Motor Supply Cable**

Max. Recommended Pulling Tension:	3088 lbs.
Min. Bend Radius (Install)/Minor Axis:	10.750 in.

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	TC-ER, Unlisted Singles, WTTC
NEC Articles:	336 - ER
CSA Specification:	1000 V AWM I/II A/B
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/13/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

**Flame Test**

UL Flame Test:	UL1685 UL Loading
CSA Flame Test:	FT4
IEEE Flame Test:	1202

**Suitability**

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Burial:	Yes
Sunlight Resistance:	Yes
Oil Resistance:	Yes

**Plenum/Non-Plenum**

Plenum (Y/N):	No
---------------	----

**Electrical Characteristics (Overall)****Nom. Characteristic Impedance:**

Impedance (Ohm)

46

**Nom. Inductance:**

Inductance (μH/ft)

.153

**Nom. Capacitance Conductor to Conductor:**

Capacitance (pF/ft)

40

**Nom. Capacitance Cond. to Other Conductor & Shield:**

Capacitance (pF/ft)

72

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)

0.16

**Max. Operating Voltage - UL:**

Voltage

**29507 Multi-Conductor - 1000V UL Flexible Motor Supply Cable**

1000 V RMS (Flexible Motor Supply Cable)

600 V RMS (NEC Type TC)

**Max. Recommended Current:****Current**

130 Amps per conductor @ 30°C (per NEC)

**Related Documents:**

No related documents are available for this product

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
29507 0101000	1,000 FT	1,766.000 LB	BLACK	C Z	#2/4C XLPE SHPVC
29507 0102000	2,000 FT	3,504.000 LB	BLACK	C Z	#2/4C XLPE SH PVC
29507 010250	250 FT	437.750 LB	BLACK	C Z	#2/4C XLPE SHPVC
29507 010500	500 FT	908.000 LB	BLACK	C Z	#2/4C XLPE SHPVC

**Notes:**

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 1    Revision Date: 10-19-2011

© 2012 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.