

For more Information
please call

1-800-Belden1



General Description:

Neoprene insulation has good heat aging characteristics and is an excellent low-cost motor lead wire. It may be considered for use in hazardous locations and is being used in explosion-proof motors recognized by UL.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
1	18	16x30	TC - Tinned Copper

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Trade Name	Min. Avg. Wall (in.)
Neoprene	0.030

Overall Insulation

Overall Cable

Overall Nominal Diameter: 0.109 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +90°C

Bulk Cable Weight: 10 lbs/1000 ft.

Recommended Maximum Baking Cycles: 24 Hours @ 300°F (149°C) ~ 8 Hours @ 325°F (163°C) ~ 15 Minutes @ 450°F (232°C)

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

UL Rating: 300 V RMS, 90°C Dry, 60°C Oil

UL Type: AWM 3044

CSA Rating: 300 V RMS, 90°C

EU Directive 2011/65/EU (ROHS II): Yes

CSA Type: CL902

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Flame Test

Other Flame Test: UL Horizontal Flame

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
6.000

Max. Operating Voltage - UL:

Voltage	Description
300 VRMS	UL AWM 3044

Max. Recommended Current:

Description	Current
Single Conductor in Free Air @ 30C Ambient	18 amps

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
31518 0015000	5,000 FT	55.000 LB	BROWN	C I U Z	#18 STR CR BRN
31518 0025000	5,000 FT	55.000 LB	RED	C I U Z	#18 STR CR RED
31518 0045000	5,000 FT	55.000 LB	YELLOW	C I U Z	#18 STR CR YEL
31518 0055000	500 FT	6.000 LB	GREEN, DARK	F	#18 STR CR 90C 300V
31518 0055000	5,000 FT	55.000 LB	GREEN, DARK	C I U Z	#18 STR CR DGRN
31518 0062000	2,000 FT	22.000 LB	BLUE, LIGHT	I U	#18 STR CR 90C 300V
31518 0065000	5,000 FT	55.000 LB	BLUE, LIGHT	C I U Z	#18 STR CR LBLU
31518 0095000	5,000 FT	55.000 LB	WHITE	C I U Z	#18 STR CR WHT
31518 0102000	2,000 FT	22.000 LB	BLACK	C 1	#18 STR CR 90C 300V
31518 0105000	500 FT	6.000 LB	BLACK	F	#18 STR CR 90C 300V
31518 0105000	5,000 FT	55.000 LB	BLACK	C I U Z	#18 STR CR BLK

Notes:

C = CRATE REEL PUT-UP.
 F = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'
 I = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 200'
 U = TOPCOAT ADDERS ON STOCK SOLID COLORS. MINIMUM ORDER 10000' PER COLORCOMBINATION. (SEE TOPCOAT ADDER TABLE)
 Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.
 1 = FINAL PUT-UP LENGTH MAY VARY -20% TO +10% FROM LENGTH SHOWN.

Revision Number: 1 Revision Date: 08-30-2013

© 2016 Belden, Inc.
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.