





UPC Code: 078477795804 Country Of Origin: United States

NEMA:

4779-C

15 Amp, 277 Volt, NEMA L7-15R, 2P, 3W, Locking Connector, Industrial Grade, Grounding - BLACK-WHITE

Leviton's industry leading locking devices, such as our Black &White line of industrial grade plugs and connectors and receptacles, offer superior performance, long lasting reliability and other features that are backed by a lifetime warranty.

Technical Information

AC Horsepower Ratings Horsepower Rating: 2 HP

Electrical Specifications Amperage: 15 A

Current Interrupting: Certified for current interrupting at full rated current

Dielectric Voltage: Withstands 2000V per UL498

Grounding: Grounding

Pole: 2

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 277 VAC

Environmental Specifications

Environment: Dry

Flammability: Rated HB or better UL94 Operating Temperature: -40°C to 60°C

Material Specifications

Assembly Screws: Steel, Zinc Plated

Back Cover: Thermoplastic Blades/Contacts: Solid Brass

Body Material: Impact Modified Nylon

Clamp Insert: Nylon

Color: Black-White Cord-Clamp: Nylon Terminal Screws: Brass Wire Module: Nylon

Mechanical Specifications Cord Range: 0.230 to 0.685 Product ID: Ratings and NEMA I.D. permanently marked on device Terminal Accom.: 18-10 AWG

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Wire Gauge: 18-10 AWG

Product Features

Brand: Black and White Color: Black-White **NEMA: L7-15R**

Standards and Certifications

ANSI: C-73


CSA C22.2 No. 42: File LR-406

NEMA: WD-6 NOM Certified: 057


UL Fed Spec WC-596: File E13393

Warranty: Lifetime Warranty

Dimensional Diagram



Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:temperature} \textbf{Telephone: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

