



ezDISTRIBUTION™ | Indoor-Outdoor Tight Buffered Riser and Plenum Rated Cables



This versatile indoor-outdoor flame-rated cable design combines standards compliant performance with the direct connectorization simplicity afforded by tight buffered fibers. These cables provide an effective solution for interbuilding and building transition applications utilizing field installable connectors.

Overview

Prysmian's ezDISTRIBUTION cable family packages up to 144 color-coded 900 µm tight buffered fibers into a single flame retardant cable. This cable design is available in both riser rated and plenum rated versions for deployment in any inside plant fire-code application. The UV-resistant outer jacket, coupled with dry waterblocking technology, address environmental concerns for outdoor use. The tight buffered distribution cable supports standard installation practices and may be easily terminated using established field connectorization methods.


Product Snapshot

Applications	Versatile indoor-outdoor tight buffered cable for use with field installable connectors.
Constructions	Single-Unit (≤ 24f); Subunits (≥ 18f); interlock armor optional
Flame Ratings	Riser (OFNR / OFCR / FT4); Plenum (OFNP / OFCP / FT6)
Fiber Count	2 to 144 fibers (riser) / 2 to 96 (plenum)
Fiber Types	Single-mode (ESMF, bend-insensitive) multimode (62.5/125-OM1, 50/125- OM2+, OM3 & OM4)
Standards	TIA/EIA-568, ANSI/ICEA S-83-596, ANSI/ICEA S-104-696, UL-1666, NFPA 262, CSA 22.2 Telcordia GR-409, Telcordia GR-20, CE RoHS Compliant
Registered Supplier	ISO 9001, ISO 14001, TL 9000, and OHSAS 18001

Flame Retardant Jacket

Water Blocking Strength Members

Optical Fibers



Feature and Benefits

- 900 µm tight buffered fibers designed to support rapid field termination
- Industry standard color coding for quick, error-free fiber identification
- Single-Unit designs provide space savings and cost advantages
- Subunit construction improves organization and termination practices
- Available with bend-insensitive single-mode and multimode optical fibers
- Flexible, flame-retardant and UV-stable outer jacket
- Optional Interlock Armor provides robust protection and supports one-step installation
- Supports all high performance networks including OM4/10 Gigabit Ethernet systems



ezDISTRIBUTION™ | Indoor-Outdoor Tight Buffered

Riser and Plenum Rated Cables

ezDISTRIBUTION | Indoor-Outdoor Riser | C1181 Series | OFNR/FT4

Fiber Count	Fibers Per Subunit	Diameter inches (mm)	Cable Weight lb/kft (kg/km)	Bend Radius Load inches (cm)	Bend Radius No Load inches (cm)	Max Installation Load (Pull Strength) lbs (newtons)	Max Operation Load lbs (newtons)
2	single-unit	0.19 (4.8)	15 (22)	3.8 (9.7)	1.9 (4.9)	100 (445)	30 (133)
4	single-unit	0.22 (5.6)	19 (28)	4.4 (11.2)	2.2 (5.6)	100 (445)	30 (133)
6	single-unit	0.24 (6.0)	21 (31)	4.8 (12.2)	2.4 (6.1)	100 (445)	30 (133)
8	single-unit	0.25 (6.2)	23 (34)	5.0 (12.7)	2.5 (6.4)	100 (445)	30 (133)
12	single-unit	0.28 (7.0)	30 (45)	5.6 (14.3)	2.8 (7.2)	150 (666)	45 (200)
18	single-unit	0.305 (7.7)	36 (53)	6.1 (15.5)	3.0 (7.6)	300 (1335)	90 (400)
24	single-unit	0.32 (8.1)	43 (64)	6.4 (16.3)	3.2 (8.2)	300 (1335)	90 (400)
18	6	0.53 (13.5)	103 (153)	11.2 (28.5)	5.6 (14.3)	600 (2670)	180 (801)
24	6	0.53 (13.5)	103 (153)	11.2 (28.5)	5.6 (14.3)	600 (2670)	180 (801)
36	6	0.66 (16.8)	160 (238)	13.2 (33.6)	6.6 (16.8)	600 (2670)	180 (801)
48	12	0.66 (16.8)	140 (209)	13.2 (33.6)	6.6 (16.8)	600 (2670)	180 (801)
60	12	0.74 (18.8)	171 (254)	14.8 (37.6)	7.4 (18.8)	600 (2670)	180 (801)
72	12	0.80 (20.3)	208 (309)	16.0 (40.7)	8.0 (20.4)	600 (2670)	180 (801)
96	12	0.95 (24.2)	296 (441)	19.0 (48.3)	9.5 (24.2)	600 (2670)	180 (801)
144	12	1.02 (25.9)	347 (516)	20.4 (51.9)	10.2 (25.9)	600 (2670)	180 (801)

Note: Cable damage may occur if installation temperature limits are exceeded; therefore, Prysmian Group recommends storing I/O cables in appropriate temperature conditions ≥ 24 hours prior to placement.

Temperature Range

Shipping and Storage: (Riser) -40° F to +176° F (-40° C to +80° C)
 (Plenum) -40° F to +176° F (-40° C to +80° C)

Installation: (Riser) +14° F to +140° F (-10° C to +60° C)
 (Plenum) +32° F to +140° F (0° C to +60° C)

Operation: (Riser) -40° F to +176° F (-40° C to +80° C)
 (Plenum) -40° F to +176° F (-40° C to +80° C)

ezDISTRIBUTION™ | Indoor-Outdoor Tight Buffered

Riser and Plenum Rated Cables

ezDISTRIBUTION | Indoor-Outdoor Plenum | C1182 Series | OFNP/FT6

Fiber Count	Fibers Per Subunit	Diameter inches (mm)	Cable Weight lb/kft (kg/km)	Bend Radius Load inches (cm)	Bend Radius No Load inches (cm)	Max Installation Load (Pull Strength) lbs (newtons)	Max Operation Load lbs (newtons)
2	single-unit	0.18 (4.5)	9 (13)	3.6 (9.2)	1.8 (4.6)	100 (445)	30 (133)
4	single-unit	0.18 (4.6)	14 (21)	3.6 (9.2)	1.8 (4.6)	100 (445)	30 (133)
6	single-unit	0.20 (5.0)	15 (22)	4.0 (10.2)	2.0 (5.1)	100 (445)	30 (133)
8	single-unit	0.20 (5.2)	18 (27)	4.0 (10.2)	2.0 (5.1)	100 (445)	30 (133)
12	single-unit	0.24 (6.1)	22 (33)	4.8 (12.2)	2.4 (6.1)	150 (666)	45 (199.8)
18	single-unit	0.26 (6.5)	32 (48)	5.1 (13.0)	2.6 (6.5)	150 (666)	45 (199.8)
24	single-unit	0.30 (7.6)	42 (62)	6.0 (15.3)	3.0 (7.7)	150 (666)	45 (199.8)
18	6	0.41 (10.4)	86 (128)	8.2 (20.9)	4.1 (10.5)	400 (1800)	120 (540)
24	6	0.41 (10.4)	79 (117)	8.2 (20.9)	4.1 (10.5)	400 (1800)	120 (540)
36	6	0.54 (13.9)	132 (196)	10.8 (27.5)	5.4 (13.8)	400 (1800)	120 (540)
48	12	0.55 (13.9)	140 (209)	11.0 (28.0)	5.5 (14.0)	400 (1800)	120 (540)
60	12	0.63 (16.0)	173 (257)	12.6 (32.0)	6.3 (16.0)	400 (1800)	120 (540)
72	12	0.65 (16.6)	210 (312)	13.0 (33.1)	6.5 (16.6)	600 (2670)	180 (801)
96	12	0.84 (21.3)	345 (514)	16.8 (42.7)	8.4 (21.4)	600 (2670)	180 (801)

Note: Cable damage may occur if installation temperature limits are exceeded; therefore, Prysmian Group recommends storing I/O cables in appropriate temperature conditions ≥ 24 hours prior to placement.

Temperature Range

Shipping and Storage: (Riser) -40° F to +176° F (-40° C to +80° C)
 (Plenum) -40° F to +176° F (-40° C to +80° C)


Installation: (Riser) +14° F to +140° F (-10° C to +60° C)
 (Plenum) +32° F to +140° F (0° C to +60° C)

Operation: (Riser) -40° F to +176° F (-40° C to +80° C)
 (Plenum) -40° F to +176° F (-40° C to +80° C)

Ordering Guide

The Prysmian cable part number incorporates several significant attributes involving cable design and optical performance. The appropriate part number can be configured using the process described below.

Example: ezDISTRIBUTION Tight Buffered | Indoor-Outdoor Riser (OFNR/FT4), 12 fiber subunits | 48 62.5/125 Multimode Fibers total (printed in feet)



PART NUMBER CONSTRUCTION	
1 LENGTH MARKINGS	F = Feet or M = Meters
2 PRODUCT FAMILY	<p>ezDISTRIBUTION INDOOR / OUTDOOR</p> <p>Riser-FT4 C1181 = ezDISTRIBUTION Indoor/Outdoor Riser Tight Buffer Flame Rating: OFNR/FT4 Fiber Count 2 to 144</p> <p>Plenum-FT6 C1182 = ezDISTRIBUTION Indoor/Outdoor Plenum Tight Buffer Flame Rating: OFNP/FT6 Fiber Count 2 to 96</p>
3 CONSTRUCTION	<p>(blank) = none</p> <p>AJ = Aluminum Jacketed</p> <p>SJ = Steel Jacketed</p>
4 FIBER GROUPING	<p>00 = single-unit</p> <p>06 = 6f per subunit</p> <p>12 = 12f per subunit</p>

FIBER INFORMATION					
5 FIBER TYPE					
SINGLE-MODE					
HB = Single-Mode (ITU G.652 C & D) Low Water Peak					
ES = Enhanced Single-Mode (ITU G.652 C & D)					
CE = Corning™ SMF28e+ Single-Mode					
B1 = Bend-Insensitive Single-Mode (ITU G.657.A1 & G.652.D)					
B2 = Bend-Insensitive Single-Mode (ITU G.657.A2 & .B2, & G.652.D)					
MULTIMODE					
	Wavelength (nm)	Bandwidth (MHz)	1 GbE Dist (m)	10 GbE Dist (m)	
G6 = OM1 (62.5µm)	850/1300	200/500	300/550	33/___	
G5 = OM2+ BIF (50µm)	850/1300	700/500	800/550	150/___	
G3 = OM3 BIF (50µm)	850/1300	1500/500	1000/550	300/___	
G4 = OM4 BIF (50µm)	850/1300	3500/500	1100/550	550/___	
6 FIBER COUNT					
002 to 144 fibers -Riser					
002 to 096 fibers -Plenum					
7 FIBER GRADE					
SINGLE-MODE					
Attenuation (dB/km)	Wavelength (nm)	Fiber Type			
EB = 0.7/0.7/0.7	1310/1383/1550	Enhanced Single-Mode			
EA = 0.5/0.5/0.5	1310/1383/1550	Bend-Insensitive Single-Mode			
E7 = 0.4/0.4/0.3	1310/1383/1550	Bend-Insensitive Single-Mode			
MULTIMODE					
Attenuation (dB/km)	Wavelength (nm)	Fiber Type			
M2 = 3.5/1.0	850/1300	OM1 (62.5µm)			
M3 = 3.0/1.0	850/1300	OM2+, OM3, OM4 (50µm)			
Other cable constructions and fiber performance grades available on request.					

© DRAKA & PRYSMIAN - Brands of The Prysmian Group. 2016 All Right Reserved. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed correct at the time of issue. Prysmian Group reserves the right to amend any specifications without notice. These specifications are not contractually valid unless specifically authorized by Prysmian Group. Issued October 2016.