

Liquidtight Flexible Metal Conduit Fittings T&B Catalog Number:

5265

UPC Number: 78621005265

Status: Active

Description:

Liquidtight Sealing Gasket, 1-1/4 Inch, with 316 Stainless Steel Retainer and Santoprene Sealing Material

and Santopiene Sealing Wi	ateriai
Features	
	Design locks resilient sealing material in steel.
	Steel retainer protects seal from extruding out un- der torque and limits compression to an optimum predetermined value; provides high quality seal.
	Resilient material flows and seals rough edges.
Application	
	When used with an externally threaded connector provides a tight seal against oil, fumes or moisture at the knockout opening.
General	
Trade Size (inches)	1 1/4
Material	Stainless Steel
Dimension Information	
Dimension A (inches)	2.15
Dimension B (inches)	0.22
Specifications	
3dmodel	Available on Website
Packaging	
T&B Inner Pack	5
Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	2.5 lbs. per 100
Application Support	
T&B Sales Drawings	wsd-001558
Certifications	
RoHS Compliance	Yes
Certifications	



File Nbr: E 13938

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com