



Project: Glenn Smith (seal ring)

Location: Houston

CNP

Liquidtight Flexible Metal Conduit Fittings

T&B Catalog Number:

5266

UPC Number:

78621005266

Status:

Active

Description:

Liquidtight Sealing Gasket, 1-1/2 Inch, with 316 Stainless Steel Retainer and Santoprene Sealing Material

Features

Design locks resilient sealing material in steel.

Steel retainer protects seal from extruding out under torque and limits compression to an optimum predetermined value; provides high quality seal.

Resilient material flows and seals rough edges.

Application

When used with an externally threaded connector provides a tight seal against oil, fumes or moisture at the knockout opening.

General

Trade Size (inches) 1 1/2

Material Stainless Steel

Dimension Information

Dimension A (inches) 2.42

Dimension B (inches) 0.23

Specifications

3dmodel Available on Website

Packaging

T&B Inner Pack 5

Package in Units 25

T&B Sold in UOM Each

T&B Weight Per UOM 3 lbs. per 100

Application Support

T&B Sales Drawings wsd-001558

Certifications

RoHS Compliance Yes

Certifications



File Nbr:

E 13938

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com