

Insulated multi-taps

AMT multi-port connector “same side” (continued)

AMT aluminum splice (continued)






Diagrams	Cat. no.	Fig.	No. of ports	Wire range (AWG or kcmil)	Length (in.)	Width (in.)	Height (in.)	Hex size (in.)	Std. pkg. qty.
	AMTS25068	4	8	250–6 Str.	7.53	1.91	2.17	5/16	3
	AMTS25069	4	9	250–6 Str.	8.42	1.91	2.17	5/16	3
	AMTS250610	4	10	250–6 Str.	9.32	1.91	2.17	5/16	2
	AMTS250611	4	11	250–6 Str.	10.21	1.91	2.17	5/16	2
	AMTS250612	4	12	250–6 Str.	11.1	1.91	2.17	5/16	2
	AMTS250613	4	13	250–6 Str.	12	1.91	2.17	5/16	1
	AMTS250614	4	14	250–6 Str.	12.89	1.91	2.17	5/16	1
	AMT350	2	2	350–10 Str.	2.35	2.13	2.63	5/16	25
	AMTS35062	2	2	350–6 Str.	2.51	2.03	2.62	5/16	4
	AMTS35063	4	3	350–6 Str.	3.56	2.03	2.62	5/16	4
	AMTS35064	4	4	350–6 Str.	4.61	2.03	2.62	5/16	3
	AMTS35065	4	5	350–6 Str.	5.66	2.03	2.62	5/16	3
	AMTS35066	4	6	350–6 Str.	6.71	2.03	2.62	5/16	2
	AMTS35067	4	7	350–6 Str.	7.76	2.03	2.62	5/16	2
	AMTS35068	4	8	350–6 Str.	8.81	2.03	2.62	5/16	2
	AMTS35069	4	9	350–6 Str.	9.86	2.03	2.62	5/16	2
	AMTS350610	4	10	350–6 Str.	10.91	2.03	2.62	5/16	2
	AMTS350611	4	11	350–6 Str.	11.96	2.03	2.62	5/16	1
	AMTS350612	4	12	350–6 Str.	13.01	2.03	2.62	5/16	1
	AMTS350613	4	13	350–6 Str.	14.06	2.03	2.62	5/16	1
	AMTS350614	4	14	350–6 Str.	15.11	2.03	2.62	5/16	1
	AMT500	2	2	500–6 Str.	2.62	2.16	2.91	3/8	25
	AMTS50042	2	2	500–4 Str.	2.97	2.28	3.04	3/8	3
	AMTS50043	4	3	500–4 Str.	4.12	2.28	3.04	3/8	3
	AMTS50044	4	4	500–4 Str.	5.28	2.28	3.04	3/8	3
	AMTS50045	4	5	500–4 Str.	6.44	2.28	3.04	3/8	2
	AMTS50046	4	6	500–4 Str.	7.59	2.28	3.04	3/8	2
	AMTS50047	4	7	500–4 Str.	8.75	2.28	3.04	3/8	2
AMTS50048	4	8	500–4 Str.	9.9	2.28	3.04	3/8	2	
	AMTS50049	4	9	500–4 Str.	11.06	2.28	3.04	3/8	2
	AMTS500410	4	10	500–4 Str.	12.22	2.28	3.04	3/8	1
	AMTS500411	4	11	500–4 Str.	13.37	2.28	3.04	3/8	1
	AMTS500412	4	12	500–4 Str.	14.53	2.28	3.04	3/8	1
	AMTS500413	4	13	500–4 Str.	15.68	2.28	3.04	3/8	1
	AMTS500414	4	14	500–4 Str.	16.84	2.28	3.04	3/8	1
	AMTS7502502	4	2	750–250	3.47	2.75	3.31	1/2	3
	AMTS7502503	4	3	750–250	4.89	2.75	3.31	1/2	3
	AMTS7502504	4	4	750–250	6.32	2.75	3.31	1/2	2
	AMTS7502505	4	5	750–250	7.74	2.75	3.31	1/2	1
	AMTS7502506	4	6	750–250	9.16	2.75	3.31	1/2	1
	AMTS7502507	4	7	750–250	10.58	2.75	3.31	1/2	1
	AMTS7502508	4	8	750–250	12	2.75	3.31	1/2	1
	AMTS7502509	4	9	750–250	13.43	2.75	3.31	1/2	1
AMTS75025010	4	10	750–250	14.85	2.75	3.31	1/2	1	
AMTS75025011	4	11	750–250	16.27	2.75	3.31	1/2	1	
AMTS75025012	4	12	750–250	17.69	2.75	3.31	1/2	1	
AMTS75025013	4	13	750–250	19.11	2.75	3.31	1/2	1	
AMTS75025014	4	14	750–250	20.54	2.75	3.31	1/2	1	

Fig. 5