Technical Data Sheet Aquaseal® Communication Cables







PART NUMBER: AQC432

DESCRIPTION: 6 Pair 22 Awg. Stranded bare copper conductors, individually shielded with an Aquaseal tape and

overall jacket.

NEC RATING: CM or CL3, NEC Article 800 and 725

APPROVALS: (UL) C(UL) Listed, (ETL)us Listed

APPLICATION: Materials suitable for outdoor use, and indoor trays, allows a variety of uses for (Intercom, Security,

Sound, Audio, Background music)

Construction Parameters:

Conductor 22 AWG Bare Copper

Stranding7x30Insulation MaterialPVCInsulation Thickness0.010" Nom.Number of Conductors12 (6 Pair)

Shield 100% Aluminum Polyester Foil Drain Stranded Bare Copper

Water-Blocking Tape
2 ply water swellable each pair
Overall 2 Ply water swellable tape
Jacket Material
Sunlight/Moisture Resistance PVC

Jacket Thickness 0.025" Nom.

Overall Cable Diameter 0.520" Nom.

Approximate Cable Weight 70 Lbs/1M' Nom.

Flame Rating UL 1685 Vertical Tray

Electrical & Environmental Properties:

Temperature Rating -20deg C to 60deg C
Operating Voltage 300 V RMS

Max.Capacitance Between Conductors @ 1 KHz 55 pf/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz 99 pf/ft Nom.

DC Projectors and Conductors @ 20 loc C 17 Ohmo (IM) Nom.

DC Resistance per Conductor @ 20deg C 17 Ohms/1M' Nom.

Insulation Colors Black/Red-Red, Black/White-White, Black/Green-Green,

Black/Blue-Blue, Black/Yellow-Yellow,

Black/Brown-Brown

Jacket Color Gray
RoHS Compliant --

TIA455-82B Water Infiltration Test Compliant

Ves
UL 444 & 13 Compliant

Yes

Mechanical Properties:

Max. Recommended Pull Tension132 lbs.Min. Bend Radius (Install)5.2"

Specification Issue Date: 7/06

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.