

**5202U1 Multi-Conductor - Water-Blocked for Indoor/Outdoor Use**

For more Information  
please call

1-800-Belden1

**Description:**

16 AWG stranded (7x24) tinned copper conductors, PVC insulation, water-blocking tape, overall PVC jacket.

**Usage (Overall)**

**Suitable Applications:**

Low Voltage, Direct Burial, PLTC, FPL, Intercom, Sound, Audio

**Physical Characteristics (Overall)****Conductor**

**AWG:**

# Conductors	AWG	Stranding	Conductor Material
4	16	7x24	TC - Tinned Copper

**Insulation**

**Insulation Material:**

Insulation Material
PVC - Polyvinyl Chloride

**Outer Shield**

**Outer Shield Material:**

Outer Shield Material
Unshielded

**Outer Jacket**

**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

**Overall Cable**

**Overall Cabling Color Code Chart:**

Number	Color
1	Black
2	White
3	Red
4	Green

**Overall Cabling Separator Material:**

Waterblocking Tape

**Overall Nominal Diameter:**

0.291 in.

**Mechanical Characteristics (Overall)**

**Operating Temperature Range:** -30°C To +105°C

**UL Temperature Rating:** 105°C

**Bulk Cable Weight:** 57 lbs/1000 ft.

**Max. Recommended Pulling Tension:** 142 lbs.

**Min. Bend Radius (Install)/Minor Axis:** 3 in.

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

**5202U1 Multi-Conductor - Water-Blocked for Indoor/Outdoor Use**

NEC/(UL) Specification:	CMG, FPL, PLTC-ER
-------------------------	-------------------

CEC/C(UL) Specification:	CMG
--------------------------	-----

EU CE Mark:	Yes
-------------	-----

EU Directive 2000/53/EC (ELV):	Yes
--------------------------------	-----

EU Directive 2002/95/EC (RoHS):	Yes
---------------------------------	-----

EU RoHS Compliance Date (mm/dd/yyyy):	11/06/2006
---------------------------------------	------------

EU Directive 2002/96/EC (WEEE):	Yes
---------------------------------	-----

EU Directive 2003/11/EC (BFR):	Yes
--------------------------------	-----

CA Prop 65 (CJ for Wire & Cable):	Yes
-----------------------------------	-----

MII Order #39 (China RoHS):	Yes
-----------------------------	-----

**Flame Test**

UL Flame Test:	UL1685 FT4/IEEE 1202 Vertical Tray Flame Test
----------------	---

CSA Flame Test:	FT4
-----------------	-----

**Suitability**

Suitability - Indoor:	Yes
-----------------------	-----

Suitability - Outdoor:	Yes
------------------------	-----

Suitability - Burial:	Yes
-----------------------	-----

Sunlight Resistance:	Yes
----------------------	-----

**Plenum/Non-Plenum**

Plenum (Y/N):	No
---------------	----

**Electrical Characteristics (Overall)****Nom. Capacitance Conductor to Conductor:**

Capacitance (pF/ft)
---------------------

33.000
--------

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)
--------------------------

4.2
-----

**Max. Operating Voltage - UL:**

Voltage
---------

300 V RMS
-----------

**Max. Recommended Current:**

Current
---------

9 Amps per conductor @ 25°C
-----------------------------

**Related Documents:**

No related documents are available for this product

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
5202U1 0101000	1,000 FT	61.000 LB	BLACK	C	4 #16 PVC PVC

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 01-07-2011

© 2012 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not

## 5202U1 Multi-Conductor - Water-Blocked for Indoor/Outdoor Use

ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.