

TWO HOLE HYLUG™ CODE CONDUCTOR STANDARD BARREL (Continued)





Fig. 1




Fig. 2




Fig. 3

Catalog Number	Fig #	Conductor					Figure Dimensions			▲ Installation Tooling							Wire Strip Length
		AWG	MM²	Stud Hole Size	Stud Hole Spacing	Tongue Width	Figure Dimensions		Dieless (# of crimps)	Mechanical MD6, OUR840, MD7-34R	Hydraulic		Color Code	Die Index			
							(B)	(T)			(L)	BCT500HS, Y500CTHS			Y35, Y39, Y750, Y46*, PAT750		
YA4C-2LN	1	4 AWG	-	1/2"	1-3/4"	.83"	.81"	.12"	4.14"	Y1MR (2) Y2MR (2) MY29-3 (1) MY29-11 (1) MRC840 (1) Y644M (1)	W4CVT (1)	X4CRT (1)	U4CRT (1)	Gray	8	7/8"	
YA4C-2LN-45	2								4.10"								
YA4C-2LN-90	3								3.30"								
YA4CL-2TC14E2	1			1/4"	3/4"	.49"	.81"	.09"	2.49"								
YA4CL-2TC14E2-45	2								2.40"								
YA4CL-2TC14E2-90	3								1.66"								
YA4CL-2TC516	1			5/16"	1"	.52"	.81"	.09"	2.80"								
YA4CL-2TC516-45	2								2.69"								
YA4CL-2TC516-90	3								1.97"								
YA3CL-2TC14	1	3 AWG	25	1/4"	5/8"	.55"	.81"	.09"	2.45"		W3CRT (1)	W3CRT (1)	U3CRT (1)	White	9	15/16"	
YA3CL-2TC14-45	2								2.33"								
YA3CL-2TC14-90	3								1.55"								
YA3C-2L	1			5/16"	5/8"	.55"	.88"	.09"	2.64"								
YA3C-2L-45	2								2.52"								
YA3C-2L-90	3								1.74"								
YA3CL-2TC38	1			3/8"	1"	.58"	.88"	.08"	3.06"								
YA3CL-2TC38-45	2								2.90"								
YA3CL-2TC38-90	3								2.11"								
YA2C-2L	1	2 AWG	35	5/16"	3/4"	.60"	.88"	.11"	2.67"		W2CVT (1) W2CRT (1) X2CRT (1)	W2CVT (1) W2CRT (1) X2CRT (1)	U2CRT (1)	Brown	10	15/16"	
YA2C-2L-45	2								2.57"								
YA2C-2L-90	3								1.77"								
YA2C-2LN	1			1/2"	1-3/4"	.83"	.88"	.11"	4.27"								
YA2C-2LN-45	2								4.19"								
YA2C-2LN-90	3								3.14"								
YA2CL-2TC14	1			1/4"	5/8"	.60"	.88"	.11"	2.47"								
YA2CL-2TC14-45	2								2.38"								
YA2CL-2TC14-90	3								1.58"								
YA2CL-2TC14E1	1			1/4"	1"	.60"	.88"	.11"	2.85"								
YA2CL-2TC14E1-45	2								2.77"								
YA2CL-2TC14E1-90	3								1.96"								
YA2CL-2TC14E2	1			1/4"	3/4"	.60"	.88"	.11"	2.60"								
YA2CL-2TC14E2-45	2								2.51"								
YA2CL-2TC14E2-90	3								1.71"								
YA2CL-2TC38	1			3/8"	1"	.60"	.88"	.11"	3.03"								
YA2CL-2TC38-45	2								2.94"								
YA2CL-2TC38-90	3								2.15"								
YA2CL-2TC516	1			5/16"	1"	.60"	.88"	.11"	2.91"								
YA2CL-2TC516-45	2								2.82"								
YA2CL-2TC516-90	3								2.02"								
YA1C-2LN	1	1 AWG	50	1/2"	1-3/4"	.81"	.88"	.12"	4.32"	Y1MR (2) MY29-3 (1) MY29-11 (1) MRC840 (1) Y644M (1)	W1CVT (1) W1CRT-1 (1) X1CRT-1 (1)	W1CVT (1) W1CRT-1 (1) X1CRT-1 (1)	U1CRT-1 (1) U4CABT (1)	Green	11	15/16"	
YA1C-2LN-45	2								4.23"								
YA1C-2LN-90	3								3.36"								
YA1C-2L	1			5/16"	7/8"	.68"	.88"	.10"	2.82"								
YA1C-2L-45	2								2.71"								
YA1C-2L-90	3								1.92"								
YA1CL-2TC14	1			1/4"	5/8"	.68"	.88"	.10"	2.51"								
YA1CL-2TC14-45	2								2.40"								
YA1CL-2TC14-90	3								1.60"								
YA1CL-2TC14E2	1			1/4"	3/4"	.68"	.88"	.10"	2.64"								
YA1CL-2TC14E2-45	2								2.52"								
YA1CL-2TC14E2-90	3								1.73"								

C-45

-- Color code not assigned.
▲ See tooling section of this catalog for complete tool and die listings.

◆ For applications greater than 2000 volts consult cable manufacturer for voltage stress relief instructions.
* Use PUADP-1 adapter with "U" dies in Y46 HYPRESS™.

** P-RT die sets for use in Y46 HYPRESS™ only, PUADP-1 adapter not required.
*** The MM² conductor sizes listed are the recommendations for Class 2 conductor.