



BURNDY Catalog Number
UPC Number
Description
Status

YAV4CLTC10FX
 781810022610
 CU HYLUG 4 STR FLEX 10
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 Strip Length

Dimensional

Straight
 1.32
 Standard
 Chamfered
 0.20
 Standard
 0.09
 0.50
 0.55
 1/2

Number of Holes

General

1
 Cu Tubing Hylug; 1 Hole with
 Inspection Window; #4 WELD,
 5(91/#24)-4(105/#24) DLO, #4
 AWG Code, 40 & 50 Navy; 600V-
 35kV; #10 stud; Compression;
 0.21 in BCD

Product Description

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

4 AWG
 4 AWG
 4 AWG
 4 AWG
 5 (91/#24) DLO-4 (105/#24) DLO
 4 AWG

Physical

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Tin - Electro Plated
 #10
 Gray
 Y
 8
 Copper

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS

Y
 Y
 Compliant
 N
 N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47, industrial Park Drive
 Manchester NH03109

BURNDY Technical Servcies

47, industrial Park Drive
 Manchester NH03109

Hours: 8.00 AM - 5.00 PM
 Monday - Friday
 Phone: 000-346-4175