



BURNDY Catalog Number
UPC Number
Description
Status

YAV2CLTC12FX
 781810022795
 2FLEX 1/2 STUD
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 Strip Length

Straight
 2.12
 Standard
 Chamfered
 0.52
 Standard
 0.09
 0.63
 0.73
 11/16

General

Number of Holes

1

Product Description

Cu Comp Terminal Flex Cond, Bvl
 Entry, 1 Hole/W/InspWindow, #2
 Weld, 3(125/#24)-2(150/#24)DLO
 Flex, #2 AWG Code, 60 Navy, 600
 V-35 kV, 1/2" Stud, Std bbl

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

2 AWG
 2 AWG
 2 AWG
 2 AWG
 3 (125/#24) DLO-2 (150/#24) DLO
 2 AWG

Physical

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Tin - Electro Plated
 1/2
 Brown
 Y
 10
 Copper

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS

Y
 Y
 Compliant
 N
 N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47, industrial Park Drive
 Manchester NH03109

BURNDY Technical Servcies

47, industrial Park Drive
 Manchester NH03109

Hours: 8.00 AM - 5.00 PM
 Monday - Friday
 Phone: 000-346-4175