



Main

| | |
|---------------------------|---|
| Product or component type | Single Throw Safety Switch |
| Line Rated Current | 100 A |
| Product certifications | UL listed |
| NEMA degree of protection | NEMA 1 steel |
| Device composition | Neutral (factory installed) |
| Disconnect device type | Fusible disconnect |
| Short-circuit current | 10 kA H or K 200 kA R, J or L |
| Device mounting | Surface |
| Number of poles | 3 |
| Electrical connection | Lugs |
| Series name | Heavy duty |
| System Voltage | 600 V AC/DC |
| AWG gauge | AWG 14...AWG 1/0 (copper) AWG 12...AWG 1/0 (aluminium) |

Complementary

Environment

Offer Sustainability

| | |
|--|--|
| Green Premium product | Green Premium product |
| Compliant - since 1313 - Schneider Electric declaration of conformity | Compliant - since 1313 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Need no specific recycling operations | Need no specific recycling operations |
| WARNING: This product can expose you to chemicals including: | WARNING: This product can expose you to chemicals including: |
| Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| For more information go to www.p65warnings.ca.gov | For more information go to www.p65warnings.ca.gov |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|