

HBL5266C -- Straight Blade Products, Insulgrip Series



2-Pole 3-Wire Grounding, 15A 125V, 5-15P, Black and White Nylon

Product Specifications

Product Type



Body Style

Straight

Standard

NEMA

Amperage

15A

Voltage

125V

Poles and Wires

2 Pole, 3-Wire Grounding

Hospital Grade ?

No

Plug/Connector Grade

Insulgrip

Color



Black

NEMA No.

5-15P

Horsepower

0.5

Cord Dia.

.230"-.720" (5.8-18.3)

Type

2 Pole, 3 Wire, Grounding

Rating

15A,125V

Certification

UL Listed to UL498 File E1706, CSA Certified to C22.2 No. 42 File 280

IP Suitability

IP20

Housing Material

Nylon-Black

Blade Holder Material

Nylon-Natural

Retainer Material

Polycarbonate-Clear

Cord Clamp Material

Nylon-Natural

Contact Blades Material

.060" (1.5) Brass

Ground Contact Blade Material

.040" (1.0) Copper Alloy

Terminal Screw Material

#8-32 Brass /Ni plated for neutral

Ground Screw Material

#8-32 Brass, Multiple Drive (Green)

Dielectric Voltage

Withstands 2,000V minimum.

Current Interrupting

Certified for current interrupting at full rated current.

Temperature Rise

Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%..

Terminal Identification

Terminals identified in accordance with UL498 (Brass, White, Green).

Terminal Accommodation

#18-#10 AWG copper stranded conductor

Product Identification	Ratings are a permanent part of the device.
Flammability	UL 94 HB or better.
Operating Temperatures	Maximum continuous 75°C, minimum -40°C (w/o impact).
UPC Number	783585173009
Weight in LBs	0.350
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

