

TRAYCONTROL® 300-C TP

twisted pair, flexible, screened, oil resistant, EMC-preferred type, NFPA 79



Part no.	Cross-section mm ²	No.pairs x Outer Ø No.cores app. mm x AWG-no.	Cop. weight kg / km	Weight app. kg / km
59795	0,382	1 x 2 x 22	6,9	17,0
59796	0,382	2 x 2 x 22	9,3	37,0
59797	0,382	3 x 2 x 22	9,7	45,0
59798	0,382	4 x 2 x 22	10,5	54,0
59799	0,382	5 x 2 x 22	11,4	63,0
59800	0,382	6 x 2 x 22	12,3	73,0
59801	0,382	7 x 2 x 22	12,3	79,0
59802	0,382	8 x 2 x 22	13,2	88,0
59803	0,382	10 x 2 x 22	15,9	107,0
59804	0,382	12 x 2 x 22	16,6	122,0
59805	0,382	14 x 2 x 22	17,4	138,0
59806	0,382	15 x 2 x 22	18,2	154,0
59807	0,382	16 x 2 x 22	18,2	161,0
59808	0,382	18 x 2 x 22	19,1	198,0
59809	0,382	20 x 2 x 22	20,1	211,0
59810	0,382	22 x 2 x 22	21,0	218,0
59811	0,382	24 x 2 x 22	23,1	230,0
59812	0,382	25 x 2 x 22	23,1	239,0
59813	0,616	1 x 2 x 20	7,4	26,0
59814	0,616	2 x 2 x 20	10,0	56,0
59815	0,616	3 x 2 x 20	10,5	72,0

Part no.	Cross-section mm ²	No.pairs x Outer Ø No.cores app. mm x AWG-no.	Cop. weight kg / km	Weight app. kg / km
59816	0,616	4 x 2 x 20	11,4	92,0
59817	0,616	5 x 2 x 20	12,4	107,0
59818	0,616	6 x 2 x 20	13,4	122,0
59819	0,616	7 x 2 x 20	13,4	132,0
59820	0,616	8 x 2 x 20	15,3	144,0
59821	0,616	10 x 2 x 20	16,4	180,0
59822	0,616	12 x 2 x 20	18,3	202,0
59823	0,616	14 x 2 x 20	19,2	221,0
59824	0,616	15 x 2 x 20	20,1	232,0
59825	0,616	16 x 2 x 20	20,1	257,0
59826	0,616	18 x 2 x 20	21,2	282,0
59827	0,616	20 x 2 x 20	22,7	307,0
59828	0,616	22 x 2 x 20	23,8	322,0
59829	0,616	24 x 2 x 20	25,0	342,0
59830	0,616	25 x 2 x 20	25,0	361,0
59831	0,963	1 x 2 x 18	7,8	28,0
59832	0,963	2 x 2 x 18	10,8	57,0
59833	0,963	3 x 2 x 18	11,3	75,0
59834	0,963	6 x 2 x 18	15,4	139,0
59835	0,963	9 x 2 x 18	17,9	212,0
59836	0,963	15 x 2 x 18	21,9	358,0

Dimensions and specifications may be changed without prior notice. (RN02)