## Technical Data Sheet Miniature Audio Cable

# **WEST PENN WIRE**

2833 West Chestnut Street Washington, PA 15301 Toll Free: (800) 245-4964 Fax: (724) 222-6420 www.westpenn-wpw.com

PART NUMBER: 77510

**DESCRIPTION:** 2 Pair 22Awg, stranded tinned copper conductors, Individually shielded overall jacket.

**NEC RATING:** CM, NEC Article 800

**APPROVALS:** (UL) Listed

**APPLICATION:** Indoor for: Intercom System, Broadcast, Recording, Sound, Audio.

### **Construction Parameters:**

Conductor 22 AWG Tinned Copper

Stranding 7x30

Insulation Material Polypropylene Insulation Thickness 0.008" Nom.

Number of Conductors 4 (2 Pair Siamese Construction)

Shield Individually 100% Aluminum Polyester Foil
Drain Stranded Tinned Copper – 1 drain wire

Jacket MaterialPVCJacket Thickness0.020" Nom.Overall Cable Diameter.189Nom.Approximate Cable Weight32 Lbs/1M' Nom.

Flame Rating UL 1685

## **Electrical & Environmental Properties:**

Temperature Rating -20deg C to 60deg C

Operating Voltage

300 V RMS

Max.Capacitance Between Conductors @ 1 KHz

Capacitance Between Conductors to Shield @ 1 KHz

DC Resistance per Conductor @ 20deg C

17 Ohms/1M' Nom.

Insulation Colors

1. Black/Red, 2. White/Green

Jacket Color Gray
RoHS Compliant Yes

#### **Mechanical Properties:**

Max. Recommended Pull Tension 51 lbs.

Min. Bend Radius (Install) 1.9"

Specification Issue Date: 12/10

This document is the property of West Penn Wire. The information contained herein is considered Proprietary and not to be reproduced by any means Without written consent of West Penn Wire Standard Lengths are 1000ft.
The Jacket is sequentially footmarked.
The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.