



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YA2C2TC38E2  
 7818101595388  
 CU HYLUG-2STR-3/8X3/4C-C  
 Active

**Web Use**  
 BURNDY Product Line

Tongue Angle  
 Length (in)  
 Barrell Style  
 Bolt Hole Size (in)  
 Barrel Type  
 Thickness  
 B Length (in)  
 Pad Width (in)  
 E - in  
 Strip Length

**Dimensional**

Straight  
 3.17  
 Chamfered  
 0.39  
 Long  
 0.11  
 1.25  
 0.60  
 0.75  
 1-5/16

Number of Holes  
 Product Description

**General**

2  
 Cu Comp Terminal Code Cond, Bvl  
 Entry, 2 Hole/W/O/InspWindow,  
 #2 AWG Code, 60 Navy, 600 V-35  
 kV, 3/8" Stud, 0.75" Spacing, Lng  
 bbl, Brown, 10 Index

Flex (Class G) Size - Range  
 Flex (Class H) Size - Range  
 Flex (Class I) Size - Range  
 Copper Solid Size (Range)  
 DLO Size (Range)  
 Copper Stranded (Range)

**Conductor(s)**

N/A  
 N/A  
 N/A  
 2 AWG  
 N/A  
 2 AWG

Type of Plating  
 Bolt Hole Size  
 Color Code  
 Plated (Yes or No)  
 Index Number  
 Product Material

**Physical**

Tin - Electro Plated  
 3/8  
 Brown  
 Y  
 10  
 Copper

UL Listed  
 CSA Certified  
 ROHS Compatible  
 UL Recognized  
 CULUS  
 Industry Standards  
**Documentation**

**Approvals / Certifications**

Y  
 Y  
 Compliant  
 N  
 N  
 UL468A-468B

**For further technical assistance, please contact us**

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175