



BURNDY Catalog Number
UPC Number
Description
Status

YA2CL2TC38
7818100181700
HYLUG - 2STR-(2) 3/8STUD
Active

Web Use
BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	3.03
Tongue Type	Standard
Barrell Style	Chamfered
Bolt Hole Size (in)	0.39
Barrel Type	Standard
Thickness	0.11
B Length (in)	0.88
Pad Width (in)	0.60
E - in	1.00
Strip Length	15/16
General	
Number of Holes	2
Product Description	Copper Compression Lug, 2 Hole w/ Inspection Window, 2 AWG, 3/8" Stud, 1" Stud Hole Spacing, Short Barrel, Tin - Electro Plated
Conductor(s)	
Flex (Class G) Size - Range	N/A
Flex (Class H) Size - Range	N/A
Flex (Class I) Size - Range	N/A
Copper Solid Size (Range)	N/A
DLO Size (Range)	N/A
Copper Stranded (Range)	2 AWG
Physical	
Type of Plating	Tin - Electro Plated
Bolt Hole Size	3/8
Color Code	Brown
Plated (Yes or No)	Y
Index Number	10
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175