



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YA32LTC38FX  
 7818101440777  
 CU HYLUG-300 FLEX-3/8STD  
 Active

**Web Use**  
 BURNDY Product Line

**Dimensional**

Tongue Angle	Straight
Length (in)	2.68
Barrell Style	Chamfered
Bolt Hole Size (in)	0.39
Barrel Type	Standard
Thickness	0.19
B Length (in)	1.19
Pad Width (in)	1.40
Strip Length	1-1/4

**General**

Number of Holes	1
Product Description	Cu Comp Terminal Flex Cond, Bvl Entry, 1 Hole/W/InspWindow, 313.1 kcmil(775/#24)DLO, 300 kcmil Flex, 600 V-35 kV, 3/8" Stud, Std bbl, Red, 18 or 324 Index

**Conductor(s)**

Flex (Class G) Size - Range	300 kcmil
Flex (Class H) Size - Range	300 kcmil
Flex (Class I) Size - Range	300 kcmil
Copper Solid Size (Range)	N/A
DLO Size (Range)	313.1 (775/#24) DLO
Copper Stranded (Range)	N/A

**Physical**

Type of Plating	Tin
Bolt Hole Size	3/8
Color Code	Red
Plated (Yes or No)	Y
Index Number	18,324
Product Material	Copper

**Approvals / Certifications**

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175