



On Line Catalog



BURNDY Catalog Number
UPC Number
Description
Status

YA34L2NTC38FX
 781810044063
 CULUG-350FLEX-3/8 X 1.75
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle Straight
 Length (in) 4.63
 Barrell Style Chamfered
 Bolt Hole Size (in) 0.39
 Barrel Type Standard
 Thickness 0.23
 B Length (in) 1.27
 Pad Width (in) 1.55
 E - in 1.00
 Strip Length 1-5/16

General

Number of Holes 2
 Product Description Copper Compression Lug, 2 Hole w/ Inspection Window, 373.7 Flex, 3/8" Stud, 1-3/4" Stud Hole Spacing, Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range 350 kcmil
 Flex (Class H) Size - Range 350 kcmil
 Flex (Class I) Size - Range 350 kcmil
 Copper Solid Size (Range) N/A
 DLO Size (Range) 373.7 (925/#24) DLO
 Copper Stranded (Range) N/A

Physical

Type of Plating Tin
 Bolt Hole Size 3/8
 Color Code Blue
 Plated (Yes or No) Y
 Index Number 19,470
 Product Material Copper

Approvals / Certifications

UL Listed Y
 CSA Certified Y
 ROHS Compatible Compliant
 UL Recognized N
 CULUS N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47, industrial Park Drive
 Manchester NH03109

BURNDY Technical Servcies

47, industrial Park Drive
 Manchester NH03109

Hours: 8.00 AM - 5.00 PM
 Monday - Friday
 Phone: 000-346-4175