



BURNDY Catalog Number
UPC Number
Description
Status

YA36L2NTCFX
 7818100213477
 HYLUG 450 MCM(NOM) FLEX-
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	5.24
Tongue Type	Standard
Barrell Style	Chamfered
Bolt Hole Size (in)	0.52
Barrel Type	Standard
Thickness	0.27
B Length (in)	1.38
Pad Width (in)	1.74
E - in	1.75
Strip Length	1-3/8

General

Number of Holes	2
Product Description	Copper Compression Lug, 2 Hole w/ Inspection Window, 444.4 Flex, 1/2" Stud, 1-3/4" Stud Hole Spacing, Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range	450 kcmil
Flex (Class H) Size - Range	450 kcmil
Flex (Class I) Size - Range	450 kcmil
Copper Solid Size (Range)	N/A
DLO Size (Range)	444.4 (1100/#24) DLO
Copper Stranded (Range)	N/A

Physical

Type of Plating	Tin
Bolt Hole Size	1/2
Color Code	Brown
Plated (Yes or No)	Y
Index Number	20,299
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175