



BURNDY Catalog Number
UPC Number
Description
Status

YA38LTC38FX
 7818101563911
 CU HYLUG-500 FLEX-3/8STD
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Length (in)
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 Strip Length

Dimensional

Straight
 3.34
 Chamfered
 0.39
 Standard
 0.27
 1.45
 1.84
 1-7/16

Number of Holes
 Product Description

General

1
 Copper Compression Lug, 1 Hole
 w/ Inspection Window, 500 Flex,
 3/8" Stud, Short Barrel, Tin Plated

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

Conductor(s)

500 kcmil
 500 kcmil
 500 kcmil
 N/A
 535.3 (1325/#24) DLO
 N/A

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Physical

Tin
 3/8
 Pink
 Y
 L99
 Copper

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS

Approvals / Certifications

Y
 Y
 Compliant
 N
 N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175