



BURNDY Catalog Number
UPC Number
Description
Status

YAG28L2NTCLD
 7818100181944
 CU LUG-4/0 FLEX-LEAD PLT
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 E - in
 Strip Length

Straight
 4.65
 Standard
 Chamfered
 0.52
 Standard
 0.15
 1.03
 1.14
 1.75
 1-1/16

General

Number of Holes
 Product Description

2
 Copper Compression Lug, 2 Hole
 w/o Inspection Window, 4/0 AWG,
 1/2" Stud, 1-3/4" Stud Hole
 Spacing, Short Barrel, Lead Plated

Conductor(s)

Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 DLO Size (Range)
 Navy Cable Size (Range)
 Copper Stranded (Range)
 Flex (Class G) Size - Range
 Flex (Class M) Size - Range
 CopperWeld Stranded Size (Range)

4/0 AWG
 4/0 AWG
 4/0 (550/#24) DLO
 200 (61) Navy
 4/0 AWG
 4/0 AWG
 4/0 AWG
 4/0 E AWG-4/0 V AWG

Physical

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Lead
 1/2
 Purple
 Y
 15
 Copper

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS

Y
 Y
 Non-Compliant
 N
 N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175