



YAV25L2NT14FX

by Burndy
Catalog ID: YAV25L2NT14FX

Prop65

Flex Conductor Standard Barrel Narrow, 1/0 AWG 275/24, 1/4 in, 2.39 in L.

Two hole hylug flex conductor standard barrel narrow tongue

Product Details

General

| | |
|--------------------------------------|---|
| Application | For Flex Conductors |
| Color Code | Pink |
| Connector Type | Terminal |
| Die Index | 12 |
| Feature - Barrel Style | <ul style="list-style-type: none"> • Chamfered • Skived |
| Feature - Barrel Type | Standard |
| Material | Copper |
| Physical Attribute - Number of Holes | 2 |
| Plated | Y |
| Plating Type | Tin - Electro Plated |
| Sub Brand | TERMINALS, HYLUG |
| Trade Name | HYLUG™ |
| Type | YAV-L-NTFX |
| UPC | 781810285497 |

Dimensions

| | |
|------------------------------------|----------|
| Dimension - B Length fraction | 11/16 in |
| Dimension - B Length inch | 0.69 in |
| Dimension - Bolt Hole Size inch | 0.27 in |
| Dimension - D inch | 1.28 in |
| Dimension - Diameter Min Size inch | 1.28 in |
| Dimension - L Length Overall mm | 61 mm |
| Dimension - Length Overall inch | 2.39 in |
| Dimension - N inch | 0.31 in |
| Dimension - Outside Diameter inch | 0.56 in |
| Dimension - Pad Width inch | 0.64 in |
| Dimension - Strip Length inch | 11/16 |
| Dimension - Stud Size inch | 1/4 |
| Dimension - Z inch | 0.34 in |

| | |
|-----------------------------------|----------|
| Physical Attribute - Tongue Angle | Straight |
|-----------------------------------|----------|

Electrical Ratings

| | |
|--------------------------|-------|
| Rating - KVA | 35 kV |
| Rating - Minimum Voltage | 600 |
| Voltage - Maximum | 35000 |

Conductor Related

| | |
|--|---|
| Conductor - Copper DLO Size | 1/0 (275/#24) DLO |
| Conductor - Copper DLO Size Range | 1/0 (275/#24) DLO |
| Conductor - Copper Flex G Size | 1/0 AWG |
| Conductor - Copper Flex G Size Range | 1/0 AWG |
| Conductor - Copper Flex H Size | 1/0 AWG |
| Conductor - Copper Flex H Size Range | 1/0 AWG |
| Conductor - Copper Flex I Size | 1/0 AWG |
| Conductor - Copper Flex I Size Range | 1/0 AWG |
| Conductor - Copper Flex K Size | 1/0 AWG |
| Conductor - Copper Flex K Size Range | 1/0 AWG |
| Conductor - Copper Flex M Size | 1/0 AWG |
| Conductor - Copper Flex M Size Range | 1/0 AWG |
| Conductor - Copper Str Navy Size | 100 (61) Navy |
| Conductor - Copper Str Navy Size Range | 100 (61) Navy |
| Conductor - Copper Str Size | 1/0 |
| Conductor - Copper Str Size Range | 1/0 |
| Conductor - CopperWeld Str Size | 1/0 F AWG;1/0 G AWG;1/0 J AWG;1/0 K AWG |
| Conductor - CopperWeld Str Size Range | 1/0 F AWG-1/0 K AWG |

Certifications and Compliance

| | |
|------------------------------------|-----|
| Certification - CSA Approved | No |
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

Logistics

| | |
|-----------------------|---|
| Minimum Pack Quantity | 1 |
|-----------------------|---|

For further technical assistance, please contact us

BURNDY Headquarters
 47 East Industrial Park Drive
 Manchester, New Hampshire 03109

Customer Service Hours:
 8 AM - 8 PM Eastern Monday-Friday
 Emergency Service 24-hours/365 Days
 Phone: 1-800-346-4175
 1-603-647-5299 (International)