



BURNDY Catalog Number
UPC Number
Description
Status

YAV25L2TC38FX90
 7818100345077
 HYDENT 1/0FLEX (2)3/8 ST
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	90 Degree
Length (in)	2.23
Tongue Type	Standard
Barrell Style	Chamfered,Skived
Bolt Hole Size (in)	0.39
Barrel Type	Standard
Thickness	0.12
B Length (in)	0.69
Pad Width (in)	0.83
E - in	1.00
Strip Length	11/16

General

Number of Holes	2
Product Description	Cu Tubing Hylug, 2 Holes with Inspection Window, 1/0 AWG Flex,100 Navy, 600V-35kV, 3/8" stud, Standard, Compression, 0.40 in BCD, Pink

Conductor(s)

Flex (Class G) Size - Range	1/0 AWG
Flex (Class H) Size - Range	1/0 AWG
Flex (Class I) Size - Range	1/0 AWG
Copper Solid Size (Range)	N/A
DLO Size (Range)	1/0 (275/#24) DLO
Copper Stranded (Range)	1/0

Physical

Type of Plating	Tin
Bolt Hole Size	3/8
Color Code	Pink
Plated (Yes or No)	Y
Index Number	12
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175