



BURNDY Catalog Number
UPC Number
Description
Status

YAV28L2NT38FX
 7818100357644
 HYLUG-4/0FLEX-NARROW TNG
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	3.43
Tongue Type	Standard
Barrell Style	Chamfered,Skived
Bolt Hole Size (in)	0.39
Barrel Type	Standard
Thickness	0.15
B Length (in)	1.03
Pad Width (in)	0.94
E - in	1.00
Strip Length	1-1/16

General

Number of Holes	2
Product Description	Copper Compression Lug, Narrow Tongue, 2 Hole, 4/0 AWG, 3/8" Stud, 1" Stud Hole Spacing, Short Barrel, Tin - Electro Plated

Conductor(s)

Flex (Class G) Size - Range	4/0
Flex (Class H) Size - Range	4/0
Flex (Class I) Size - Range	4/0
Copper Solid Size (Range)	N/A
DLO Size (Range)	4/0 (550/#24)
Copper Stranded (Range)	4/0

Physical

Type of Plating	Tin - Electro Plated
Bolt Hole Size	3/8
Color Code	Purple
Plated (Yes or No)	Y
Index Number	15
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175