



BURNDY Catalog Number
UPC Number
Description
Status

YAV29L2NT38FX
 7818102777377
 CULUG-4/0FX-3/8ST Yellow
 Active

Web Use
 BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	3.43
Barrell Style	Chamfered
Barrel Type	Standard
Thickness	0.16
B Length (in)	1.03
Pad Width (in)	0.94
E - in	1.00
Strip Length	1-1/16
General	
Number of Holes	2
Product Description	Copper Compression Lug, Narrow Tongue, 2 Hole w/ Inspection Window, 4/0 Flex, 3/8" Stud, 1" Stud Hole Spacing, Short Barrel, Tin - Electro Plated
Conductor(s)	
Flex (Class G) Size - Range	N/A
Flex (Class H) Size - Range	N/A
Flex (Class I) Size - Range	N/A
Copper Solid Size (Range)	N/A
DLO Size (Range)	4/0 (550/#24) DLO
Copper Stranded (Range)	4/0 AWG
Physical	
Type of Plating	Tin - Electro Plated
Bolt Hole Size	3/8
Color Code	Yellow
Plated (Yes or No)	Y
Index Number	16
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175