



BURNDY Catalog Number
UPC Number
Description
Status

YAV2CLNT14FX
 7818103261388
 2FLEX 1/4STUD NARROW
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	1.71
Barrell Style	Chamfered
Bolt Hole Size (in)	0.27
Barrel Type	Standard
Thickness	0.10
B Length (in)	0.63
Pad Width (in)	0.46
Strip Length	11/16

General

Number of Holes	1
Product Description	Flex Conductor Standard Barrel Narrow, #2 AWG #2 Weld 125/24 150/24, 1/4 in, 1.71 in L

Conductor(s)

Flex (Class G) Size - Range	2 AWG
Flex (Class H) Size - Range	2 AWG
Flex (Class I) Size - Range	2 AWG
Copper Solid Size (Range)	2 AWG
DLO Size (Range)	3 (125/#24) DLO-2 (150/#24) DLO
Copper Stranded (Range)	2 AWG

Physical

Type of Plating	Tin - Electro Plated
Bolt Hole Size	1/4
Color Code	Brown
Plated (Yes or No)	Y
Index Number	10
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175