


[On Line Catalog](#)


BURNDY Catalog Number
UPC Number
Description
Status

YAV6CLTC14FX90
 781810022849
 CUHYLUG 6STRFLEX1/4STUD
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 Strip Length

Dimensional

90 Degree
 0.88
 Standard
 Chamfered
 0.27
 Standard
 0.08
 0.50
 0.48
 1/2

Number of Holes

General

1
 Cu Tubing Hylug; 1 Hole with
 Inspection Window; #6 WELD,
 6(61/#24) DLO, #6 AWG Code, 30
 Navy; 600V-35kV; 1/4" stud;
 Standard; Compression; 0.27 in
 BCD; Blue

Product Description

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

6 AWG
 6 AWG
 6 AWG
 6 AWG
 6 (61/#24) DLO
 6 AWG

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Physical

Tin - Electro Plated
 1/4
 Blue
 Y
 7
 Copper

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS

Y
 Y
 Compliant
 N
 N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47, industrial Park Drive
 Manchester NH03109

BURNDY Technical Servcies

47, industrial Park Drive
 Manchester NH03109

Hours: 8.00 AM - 5.00 PM
 Monday - Friday
 Phone: 000-346-4175