



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YAZ382TC38FX  
 7818101353899  
 HYLUG-LONG W/PORT-500FLX  
 Active

**Web Use**  
 BURNDY Product Line

Tongue Angle  
 Strip Length  
 Length (in)  
 Barrell Style  
 Bolt Hole Size (in)  
 Barrel Type  
 Thickness  
 B Length (in)  
 Pad Width (in)  
 E - in

**Dimensional**

Straight  
 2-7/8  
 5.72  
 Skived  
 Long  
 0.27  
 2.81  
 1.84  
 1.00

Number of Holes  
 Product Description

**General**

2  
 Cu Comp Terminal Flex Cond, Bvl  
 Entry, 2 Hole/W/InspWindow,  
 535.3 kcmil(1325/#24)DLO, 500  
 kcmil Flex, 600 V-35 kV, 3/8"  
 Stud, 1.00" Spacing, Lng bbl

Copper Solid Size (Range)  
 Navy Cable Size (Range)  
 Copper Stranded (Range)

**Conductor(s)**

N/A  
 N/A  
 N/A

Type of Plating  
 Bolt Hole Size  
 Color Code  
 Plated (Yes or No)  
 Index Number  
 Product Material

**Physical**

Tin  
 3/8  
 Pink  
 Y  
 L99  
 Copper

UL Listed  
 CSA Certified  
 ROHS Compatible  
 UL Recognized  
 CULUS

**Approvals / Certifications**

Y  
 Y  
 Compliant  
 N  
 N

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175