



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YGL34C29  
 7818102200477  
 250-500 TO 2-250 GRD GRI  
 Active



**Web Use**  
 BURNDY Product Line

Length (in)  
 B Length (in)

**Dimensional**  
 2.50  
 0.75

**General**

Copper Compression Cross Grid  
 Connector, 250 kcmil - 500 kcmil  
 or 5/8" - 3/4" Ground Rod or # 5 -  
 6 Rebar, 2 AWG (Str.) - 250 kcmil  
 Y

**Other**

Penetrox E

**Approvals / Certifications**

Product Description

Y  
 Y  
 Y  
 Compliant  
 N  
 N  
 UL467,IEEE 837

Prefilled (Oxide Inhibitor)

Type of Oxide Inhibitor

Rated for Direct Burial

UL Listed

CSA Certified

ROHS Compatible

UL Recognized

CULUS

Industry Standards

**Conductor(s)**

Rod Size (Side A) - Range  
 Rod Size (Side B) - Range  
 Rebar Size (Side B) - Range  
 Copper Solid Size (Side A) - Range  
 Copper Str Size(Side B) - Range  
 Copper Str Size (Side A) - Range  
 CopperSolid Size (Side B) - Range  
 Rebar Size (Side A) - Range


5/8 in-3/4 in  
 N/A  
 N/A  
 N/A  
 2 AWG-250 kcmil  
 250 kcmil-500 kcmil  
 N/A  
 5 -6

**Physical**

Type of Plating  
 Plated (Yes or No)  
 Index Number  
 Product Material

Unplated  
 N  
 997,998  
 Copper

**Documentation**



**For further technical assistance, please contact us**

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175